LIGHTING CONTROLS **EXTERNAL PIRS**

PROTON MULTI-DIRECTIONAL 180° PIR, IP65



FEATURES:

- Manual over ride with automatic reset after 8 hours
- Passive infra red ensures light is switched on when sensor detects movement of heat, switched off when area is vacated. Minimises false / unwanted triggering
- Large terminals accept 2 x 1.5mm2 conductors in each terminal. Facility for loop in loop out
- 3 wire multiple sensors can be wired in parallel
- High load contact rating, allows numerous fittings to be switched
- No minimum load requirements
- Complete with accessory shield to reduce detection angle





54

0P


220 240

OPERATING


SAFETY




White	RPR180PIR-01		
Black	RPR180PIR-04		
Detection Area:	180°		
Motion Detection Range:	12m diameter at 2.5m		
Loading:	Max 300W fluorescent		
	Max 300W LED		
	Max 1,200W incandescent		
Time Settings:	10 sec to 15 minutes		
	adjustable		
Lux Settings:	3-2000lx		
Weight (kg):	0.16		
Box Qty:	1		



DIMENSIONS (mm)	Height	Width	Depth
RPR180PIR-01	51	80	118
RPR180PIR-04	51	80	118





ACCESSORIES

RPRBRK-01 RPRBRK-04 Corner mount accessory, white Corner mount accessory, black