

MILD STEEL GENERAL PURPOSE WALL MOUNT

Features

- IP66
- Body construction 1.2/1.5mm
- Grey RAL7035 epoxy UV resistant polyester powder coat
- Universal enclosure
- Adjustable inner door kits and escutcheon options
- Concealed hinges
- Fully welded construction
- Polyurethane gasket
- 8mm ZDC square drive spanner lock chrome plated
- 2mm galvanised mounting pan
- Blind nutsert fasteners
- Mild steel mounting brackets
- Earth strap kit



Typical Applications



General Purpose Wall Mount Enclosures Selection Table

Model No.	Height	Dimensions (mm)		Useable Depth
		Width	Depth	
PMX302015	300	200	150	132
PMX302515	300	250	150	132
PMX303015	300	300	150	132
PMX403015	400	300	150	132
PMX504016	500	400	160	142
PMX302520	300	250	200	182
PMX303020	300	300	200	182
PMX403020	400	300	200	182
PMX404020	400	400	200	182
PMX504020	500	400	200	182
PMX505020	500	500	200	182
PMX604020	600	400	200	182
PMX605020	600	500	200	182
PMX606020	600	600	200	182
PMX705020	700	500	200	182
PMX806020	800	600	200	182
PMX606030	600	600	300	282
PMX705025	700	500	250	232
PMX806030	800	600	300	282

Available in powdercoat orange RAL2000 on request

General Purpose Wall Mount Enclosures Selection Table Continued

Model No.	Dimensions (mm)			Useable Depth
	Height	Width	Depth	
PMX808030	800	800	300	282
PMX1006030	1000	600	300	282
PMX1008032	1000	800	320	302
PMX1206030	1200	600	300	282
PMX1208030	1200	800	300	282
PMX806040	800	600	400	382
PMX808040	800	800	400	382
PMX1008040	1000	800	400	382
PMX1206040	1200	600	400	382
PMX1208040	1200	800	400	382
PMX1408040	1400	800	400	382



*Modular consoles, control desks and custom mild steel enclosures available on request