

### Main

Body type	Deep box
Device short name	AW
Head type	Plunger head top
Series name	Heavy duty

### Complementary

[In] rated current	10 A
Body material	Cast zinc
Cable entry	Conduit entry 1 20 mm
Contact form	Form ZZ DPDT-DB
Contacts operation	Snap action
Contacts type and composition	2 NO/2 NC
Electrical connection	Screw clamp terminal
Impregnation material	Oil
Material	Iron roller
Mounting location	Front Rear
Operating distance	0.19...0.31 inch
Operating travel	0.05 in 0.09 in
Permissible voltage	<= 600 V
Size	0.63 x 0.25 inch roller
Switch actuation	Horizontal
Torque value	3 lbf.in
Type of operator	Momentary Spring return roller

### Environment

ambient air temperature for operation	0...185 °F
NEMA degree of protection	NEMA 1/2/4/12/13
product certifications	CE CSA LR25490 class 3211 03 UL listed file E42259 CCN NKCR

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be Compliant
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.