Product data sheet Characteristics

EVP2CNS321C4

Attached Cable T2 32A 1-Ph IEC 4 meters -Wallbox EVH2 spare part



Main Range **EVlink** Product or component Charging cable Accessory / separate Spare part part category Network number of Single phase phases Poles description 1P + N [In] rated current 32 A [Us] rated supply 220...240 V AC 50/60 Hz voltage Compatible TN Earthing system Compatible TT Compatible IT with additional isolation transformer on

the power supply 7.4 W 32 A

Complementary

Connector type	T2 vehicle end silver plated contacts Without connector charging station end	
Range compatibility	EVlink EVlink Wallbox EVH2 charging station	
Standards	IEC 62196-2 IEC 62196-1	
Product certifications	CE	
Length	4 m	
Net weight	3.1 kg	

Nominal output power Socket number

Environment

IP degree of protection	IP54 conforming to IEC 60529	
IK degree of protection	IK10 conforming to IEC 62262	
Ambient air temperature for operation	-3050 °C	
Ambient air temperature for storage	-4080 °C	
Relative humidity	595 %	

Packing Units

Offer Sustainability

•		
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant E EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	☑ China RoHS Declaration	
RoHS exemption information	₫Yes	

Life Is On