



SHROUD 3P VLB125-200SSF100-160



- Double break per pole offers high durability and short-circuit withstand
- Use of glass fibre reinforced polyester provides high mechanical and thermal resistance (does not include SLBM or VLBM modular series)
- Quick and easy to install thanks to good centre to centre distance and connection accessories including copper connecting links.
- Wide range of accessories available which is flexible in adapting to various applications and reduces the cost of management and storage
- All Socomec load break switches are compatible with the ergonomic IP65 S-Type Handles which features interlocking (in the ON position), padlocking, UV and chemical agent resistive material and the choice of standard blue or red / yellow colour

Representative Photo Only  
(actual product may vary based on configuration selections)

**SPECIFICATIONS**

Component Type Power Distribution & Protection	Terminal Cover
Number of Poles	3
Package Quantity	1 qty
Details, Switch	SSF BS/DN 100...160A
Details, text	Top and bottom mounting position. 2 set required, 1 for line and 1 for load.
Mounting Position	Top / Bottom
IP Rating	IP20

**REFERENCES**

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	<a href="#">39983016_Manufacturer Product Selection Guide</a>